

## Patent Abstracts of Japan

PUBLICATION NUMBER : 07224734  
PUBLICATION DATE : 22-08-95


APPLICATION DATE : 15-02-94  
APPLICATION NUMBER : 06018376

APPLICANT : TOYOTA MOTOR CORP;

INVENTOR : MATSUURA KOZO;

INT.CL. : F02M 37/00 B60K 15/03 F02M 25/00  
F02M 25/022

TITLE : FUEL ADDITIVE SUPPLY DEVICE



ABSTRACT : PURPOSE: To realize a fuel additive supply device for supplying a fuel additive to the fuel system of an internal combustion engine for an automobile in a simple constitution and at a low cost without electric control.

CONSTITUTION: An additive tank 1 for storing an additive is provided in the vicinity of a supply port of a fuel passage 3 to a fuel tank, the additive tank 1 and the fuel passage 3 are connected to each other by a communicating path 2, and an additive measuring chamber 14 is disposed in the midway of the communicating path 2. A non-return valve 17 is provided on the upstream side of the additive measuring chamber 14, and a pressure valve 16 is provided on the downstream side thereof. A piston 13 is disposed in the additive measuring chamber 14, and the piston 13 is connected to a fuel lid 4 by a link 43. The piston 13 is pressed by opening the fuel lid 4 to pressurize the interior of the additive measuring chamber 14 and discharge the additive. The piston 13 is pulled by closing the fuel lid 4 to reduce the pressure in the additive measuring chamber 14 and to draw the additive from the additive tank 1 into the measuring chamber 14.

COPYRIGHT: (C)1995,JPO